

KEIM Optil®-Grob Filled silica-sol interior texture paint



1. Product description

KEIM Optil-Grob is a ready-to-use, filled silica-sol interior texture paint manufactured in accordance with DIN EN 13 300 (also complies with DIN 18 363, 2.4.1 silicate emulsion paint).

2. Field of application

KEIM Optil-Grob may be used to provide filling or slightly granular textured coat on any conventional interior wall and ceiling surfaces. KEIM Optil and KEIM Optil-Grob are particularly suitable for demanding interior designs with specific requirements for color intensity and appearance in prestigious architecture and/or difficult lighting conditions. Surfaces with salt efflorescence, enamels, untreated wood and plastic wall coverings are not suitable.

3. Product properties

- Intense and lightfast color shades
- Optimized for application in areas with glancing light
- Outstanding hiding power
- Economic consumption
- Highly vapor permeable
- Non-flammable (corresponding to DIN 4102-A2, certified)
- Hinders mould growth
- Low stress
- Low environmental impact
- LEED - yes

Material characteristics

- Org. content: < 5%
- Specific weight: approx. 1.6 g/cm³
- pH-value: approx. 11
- VOC's (white or tinted) ASTM D6886: < 1 g/l

- Diffusion-equivalent air layer thickness: $s_d < 0.01 \text{ m}$
(Corresponds to water vapor diffusion density:) $V > 2100 \text{ g/m}^2\text{d}$
- Vapor permeability 75 - 85 perms

Color shade

White and KEIM's „Palette Exclusiv“ range. Additionally available in 16 monochrome shades and in the shades of KEIM's „Avantgarde“ color swatch. Custom color matching upon request.

Note: The Optil-Grob monochrome shade 9019 cinnabar red can only be produced with an organic pigment.

Optil-Grob is not available in gold and silver color shades.

Tint only with KEIM Optil-Grob monochrome shades. Optil-Grob can only be factory tinted. Texture-dependent color shade deviations are possible.

4. Application instructions

Substrate preparation and application

The substrate must be sound, solid, dry, clean and free of dust, grease, oils, salts and other substances that would prevent bonding.

Substrate and air temperature during application and drying > 41 °F (>5 °C).

Optimization of surface homogeneity of subsequent paint coats, in particular under difficult light conditions or dusting surface, can be achieved by a pretreatment with KEIM Soliprim.

In the case of glancing light conditions, the substrate must be appropriately prepared, suitable



tools must be used and greater care must be taken with application.

KEIM Optil-Grob may be applied both as a priming coat and as a finishing coat.

KEIM Optil-Grob may be applied by brush, roller or airless spraying (nozzle 0.94 mm/0.037 in.). The product should, in principle, only be diluted with clean water.

Base coat:

KEIM Optil-Grob undiluted or thinned with clean water up to 10% maximum (12oz of water/gallon of Optil-Grob).

Top coat:

KEIM Optil or KEIM Optil-Grob undiluted.

Drying times

A drying time of at least 12 hours must be left between coats.

Consumption

Approximately 290 - 340 sq.ft./gallon on a smooth surface.

The stated consumption figures are for guidance. Exact values can only be determined by painting test areas on the structure to be coated.

Cleaning of tools

Clean with water immediately after use.

5. Packaging

1 gallon, 2 gallon and 4 gallon containers.

6. Storage

12 months in sealed container under cool, frost-free conditions. Protect from heat and direct sunlight.

7. Hazardous substances ordinance class

n/a

8. Transport hazard class

n/a

9. Disposal

EC Waste Code No. 08 01 12

Any residues must be emptied out of containers before recycling.

10. Safety instructions

Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water. Protect the eyes and skin from splashes. Keep out of reach of children.

Product code: M-SK 01

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.

