



TECHNICAL DATA SHEET

KEIM INNOTOP®

INTERIOR MINERAL SOL SILICATE PAINT

1. PRODUCT DESCRIPTION

Innotop is an economical interior dispersion silicate paint for use on interior walls and ceilings. It is Cradle to Cardle® certified silver and C2C Certified Material Health Certificate™ Gold.

2. FIELD OF APPLICATION

Use for residential, light duty commercial, and historic interiors where fast production and superior hiding are required. Use on new or previously painted walls and ceilings of drywall, plaster, concrete, brick/masonry, or stucco. Do not use on lacquered surfaces, wood or substrates with salt efflorescence.

3. PRODUCT PROPERTIES

Innotop uses a water-base silica-sol potassium silicate binder and is formulated with only mineral fillers and pigments. It is completely natural and has an extremely low odor. Manufactured in accordance with DIN EN 13 300 silicate emulsion paint.

- Economical to use
- Good hiding
- AgBB-geprüft-C2C Certified Material Health Certificate™ Gold-highly permeable-
- Non-flammable (Class A2-s1,d0 as per EN 13501-1 and (ASTM) Test Method E-84 Class A building materials
- No solvents, zero VOC
- No plasticizers, preservatives or anti-microbial agents added
- No preservatives added
- Highly vapor permeable
- Easy to use—requires no specialized equipment or skill
- Hinders mold growth (certified resistance to fungi)
- Ecological with very low environmental impact
- Cradle-to-Cradle certified

Technical data

Specific Weight	1.4 - 1.7 g/cm³
Organic content	<5%
pH Value @ 20°C	11
Gloss at 85°	2.0 Matte Flat
Flashpoint	Non-Flammable
Vapor Permeability	75—85 perms
VOC (white or tinted) ASTM D6886	< 1 g/liter
Contrast ratio (hiding power) (ISO 6504-3)	Class 1 (best in class)
Wet abrasion resistance (to EN ISO 11998)	Class 3
Finish	Matte Flat (<5 gloss)
All test results performed on 2 coats Innotop applied at 300—350 SF/GAL and 7-day cure @ 77°F & 50% RH	

Color shades

White and lighter colors only.

Environmental Compliance*

EPA	YES
LEED	YES
CARB	YES
SCAQMD	YES
EPD Certified	YES
Nature Plus Certified	YES
UL Greenguard Gold	YES
C2C Material Health	Gold
Cradle to Cradle Certification	Silver

*Sustainability Data Sheet Available

4. SPECIFICATIONS/SYSTEMS

For maximum durability on bare and not previously coated surfaces, 2 coats of Innotop should be applied at recommended

coverage rates. Surface should be fully coated, with no pinholes, runs or holidays.

New Drywall or Wallboard

Self-priming 1—2 coats Innotop
Or

1 coat Mineral Wall Primer
1—2 coats Innotop

New CMU Block

1 coat Contact Plus Block Filler
1—2 coats Innotop

Unpainted Masonry, Stone or Stucco

1—2 coats Innotop

New Plaster

1—2 coats Innotop

Previously Latex or Acrylic Painted Surfaces

1—2 coats Innotop

5. SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800- 424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeling or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate acrylic primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of Innostar. Protect surfaces not to be painted (glass, natural stone, ceramics, floors,

etc.). Any splashes must be cleaned up, with soap and water, before they dry or become permanent.

Drywall

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 28 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface.

Plaster and Stucco

Bare plaster must be cured and hard.

Textured, soft, porous, or powdery plaster should be treated with a solution of 1-part KEIM Fixative and 3 parts water. Repeat until the surface is sound. Allow it to dry overnight. Stucco should be cured for 10 days.

6. APPLICATION

Mix Innotop completely with a low-speed drill and paddle attachment until homogenous with no streaks of color. Boxing mixed colors maintains color consistency from pail to pail across large surfaces.

Innotop may be applied by brush, roller, or airless spray.

- Brush - Use a nylon/polyester brush
- Roller - Use 3/8" to 3/4" nap synthetic roller cover
- Airless Spray
 - Pressure: 2000psi
 - Tip: .025 in, minimum

First coat

Innotop may be diluted up to 10% with water but is best applied as supplied. Allow it to dry 12 hours or overnight before recoating.

Topcoat

Apply Innotop as supplied. There is no recoat window after the first coat has dried.

TECHNICAL DATA SHEET – KEIM INNOPRO INTERIOR MINERAL PAINT

Cutting in: It is best to cut in small areas that can be painted before the cut-in paint dries completely, usually no more than 1 hour. Each layer of mineral paint is high build. Rolling wall paint over dried cut-in paint can lead to flashing. The double layer of paint, and different textures contribute to flashing potential. Rolling into damp cut-in minimizes flashing.

Touch Up: Use the same batch of paint and method of application for touch-up. For best touch-up results, dampening area immediately around touch-up spot. This will help to avoid a dry "edge" which can be visible in glancing light. Thin paint 10% with water and apply as sparingly as possible feathering touched up paint out and away from damaged area. Avoid high build-ups of paint during touch up.

Application conditions

Apply at temperatures between 50--86°F.

Drying times

Drying times are temperature, humidity, and coverage dependent.

Touch: 2--4 hours

Recoat: 12 hours or overnight

Coverage*

SUBSTRATE	COVERAGE*
Drywall and Wallboard	250—300 SF/GAL
Cast or Pre-Cast Concrete	225—275 SF/GAL
Brick or Stone Masonry	125—175 SF/GAL
Plaster and Stucco	100—150 SF/GAL
CMU Block (smooth)	50—100 SF/GAL

*Stated values are based on our experience on smooth surfaces. Surface texture, porosity, application conditions and type of equipment used will all vary consumption. Only a test application, using desired mixing ratio and under production conditions will forecast consumption

of the system components accurately.

Cleaning

Clean spills, spatters, hands, and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Tools should be kept in the paint material or in water during work breaks.

7. PACKAGING

4 Gallon bucket

8. STORAGE

Approx. 12 months in tightly closed container under cool, frost-free conditions. Protect from freezing, heat, and direct sunlight.

9. DISPOSAL

Dispose of completely emptied containers in accordance with local, state, and federal waste regulations. Do not pour into drains, waterways, or ground.

HAZARDOUS SUBSTANCE CLASS

n/a

10. LIMITATIONS

Do not use Innopro on floors or wood trim, cabinets, etc.

11. SAFETY INSTRUCTIONS

CAUTION! SKIN OR EYE CONTACT MAY CAUSE TEMPORARY IRRITATION

Use proper protective equipment and clothing. Wash hands and skin after handling. Keep container closed when not in use.

FIRST AID: If swallowed, give two glasses of water. Do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. In case of skin irritation, consult a physician. In

TECHNICAL DATA SHEET – KEIM INNOPRO INTERIOR M

case of contact, immediately flush eyes, and skin with plenty of water; get medical help if needed.

KEEP OUT OF REACH OF CHILDREN

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to aid in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.

The information and recommendations set forth in this Technical Data Sheet are based upon tests conducted by or on behalf of KEIM Mineral Coatings. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult <http://www.keim-usa.com/Technical-Data-Sheets> for the latest in product technical information.



Keim Mineral Coatings of America, Inc
3935 Perimeter West Drive, Suite 100
Charlotte, NC 28214
Keim-usa.com
info@keim.com
704-588-4811
©2023